





# Open your eyes to new possibilities



The world's first liquid handling system that can see

## Simplicity

#### Setup - Run - Analyse

Myra introduces a perfectly seamless workflow between the Myra liquid handling system and Mic qPCR cycler.

One setup only – configure your Mic qPCR run, tell Myra where your tubes are and watch Myra do the pipetting for you. Run files for Mic are automatically generated at the end so no need to export or import sample names, assays, thermal profiles or analysis settings.

🗸 Assays 🛛 +	Configuration Components Templates		384 Well Tip Rack 🔍 🗘 🗮	384 Well Tip Rack		
► eNOS-3	Reagents	1 0				
考 Run Setup	Name	Total Vol.				
Samples	Water	539				
South Birds	eNOS Forward Primer	83				
Deck Layout	eNOS Reverse Primer	83				
Execution	2X qPCR SYBRGreen Master Mix	672				
Reports			Myra Multipurpose Plate 🔍 🛱 🗮	Generic 96 Well 200µL PCR P 🔍 💭 🚍		
Pre-Run Report			2 2 2 2			
🔲 Mic Runs 🖬 🕷			N N N			
Run 1	Mixes	1 2				
	Name	Total Vol.				
	E eNOS-3 Intermediate Mix	1230	1 2 1 4 1 6 7 8 9 11 1 1 1 1	-000000000000		
	Component Name	Mix Vol. Required				
	Water	487	Expected run time: 0:16	Mic Plate Adapter Q Q =		
	eNOS Forward Primer	52	Tips required: 63			
	eNOS Reverse Primer	52				
	2X gPCR SY8RGreen Master Mix	641				
			Legend: Water Reagent Source Template Intermediate Mix Standard Dilution Reaction			

It's now even easier to setup experiments for multiple Mic cyclers using a single Myra liquid handling system. Then complete your analysis by combining all of your runs together using Mic's powerful Project analysis software.



### Size


At only 10 kg and with a footprint of less than 1700 cm<sup>2</sup> Myra is half the size of other in class liquid handling systems<sup>-</sup> Myra comes complete with UV LED lights and a compact HEPA filter to ensure the cleanest possible qPCR setup environment<sup>-</sup>

myra



### Pain-free calibration

With an integrated miniature camera and advanced vision technology, calibration of plasticware on Myra couldn't be simpler. Simply show Myra the centre of your well and calibration is complete. No more sticking your head under the hood and eye balling the pipette tip positions. Myra does it all for you.




### Performance



#### **Pipetting System**

Best in class accuracy and precision of < 10% for 1  $\mu$ L pipetting volumes. Myra will pipette even the smallest volumes reliably and consistently day-in, day-out. Combine this with a robust pipette head design optimised for multi-dispense and tip-reuse and your plates are loaded faster than you ever thought possible.




Perfecting the Art of Precision, Accuracy and Uniformity. A complex pattern of various dilution factors from 10 fold to as low as 1.2 fold, all achieved from the one Myra setup and Mic run.

Myra's pipette head is designed to be easily interchange-able. Easily send your head away for annual calibration to ensure your samples are always pipetted accurately. The design incorporates high precision pipette tip positioning for small aperture tubes such as 384 well plates and Mic tubes. Together with the integrated camera calibration system you can be assured Myra will always pipette inside even the smallest wells.

### State of the art technology

Myra has been designed using the latest state of the art technology. With advanced motion control systems, integrated camera and pipette monitoring systems Myra will ensure only the best results every time.

Designed directly into Myra's pipette head is a miniature pressure sensor, enabling both liquid level sensing using conventional tips as well as real time monitoring of aspirate and dispense process for errors. Be confident that all samples have been pipetted exactly as you need them.



#### **Future Proof**

It doesn't stop here. Myra has been designed for easy upgradeability. Future developments will enhance Myra's vision system to make your job even easier.





### **Specifications**

	460 mm	360 mm		(610 mm lid open)		J
Performance	Position control	Γ Closed loop, 100 μm resolution	Pipette	Volume	1 - 50 μL	
	Level detection type	Pressure sensing		Tips per rack	384	
	Calibration	High precision camera		Precision	1 μL 2 - 50 μL	< 10% CV < 1% CV
	Strategy	Single or multi-dispense		Accuracy	1 μL 2 - 50 μL	< 10% < 1%
Communication	Connection type	USB 2.0			·	
	Min. PC requirements	Intel Core i3 or equivalent				
		4 GB RAM, 5 GB disk space 1366 x 768 display	Contamination control	Tip disposal	Internal enclos	ed waste tub
Environment	Temperature range	18 - 30°C		UV decontamination	High intensity UV LED	70 mW 280 nm
	Humidity range	30 - 80%		HEPA air filtration	99.98% at 0.3	μm







info@proteigene.com